

## MATERIAL SAFETY DATA SHEET

<b>SECTION 1: PRODUCT &amp; COMPANY INFORMATION</b>			
<b>Material Identification:</b> MicroGuard AD702 Concrete Clear Waterproofing Sealer (Part A)			
<b>Adsil, Inc.</b> 1901 Mason Avenue, Suite #101 Daytona Beach, FL 32117	<b>386-274-1382 PHONE</b> <b>386-274-1798 FAX</b> <b>CHEMTREC: 1-800-424-9300</b>		
<b>SECTION 2: OSHA HAZARDOUS INGREDIENTS</b>			
<u>C.A.S. Number</u>	<u>Wt%</u>	<u>Ingredients</u>	<u>Exposure Limits</u>
Mixture – Proprietary	>98%	Alkoxysilanes	No exposure limits established
67-56-1	<2%	Methyl Alcohol	OSHA PEL (final rule) and ACGIH TLV-skin: 200 ppm, STEL 250 ppm.
<b>SECTION 3: HAZARDS IDENTIFICATION</b>			
<b>NFPA/HMIS Rating:</b> Health 1, Flammability 3, Reactivity 0 <b>Primary Routes of Entry:</b> Skin Contact, Eye Contact, Inhalation, Ingestion <b>Effects of Overexposure:</b> <b>Skin:</b> Causes skin irritation. <b>Eyes:</b> Causes eye irritation. <b>Inhalation:</b> Prolonged inhalation of spray mist can cause damage to respiratory tract. <b>Ingestion:</b> Product generates methyl alcohol, which may cause blindness and possibly death if swallowed. <b>Signs &amp; Symptoms of Exposure:</b> Burning pain in the nose and throat (inhalation), pain, redness and tearing (eye exposure), itching or burning (skin exposure).			
<b>SECTION 4: FIRST AID MEASURES</b>			
<b>Skin Contact:</b> No first aid should be needed. If itching or burning occurs, wash area with soap and water. <b>Eye Contact:</b> Immediately flush with water for 15 minutes. Get medical attention. <b>Inhalation:</b> Remove to fresh air. Get medical attention if any ill effects persist. <b>Ingestion:</b> Get immediate medical attention. If conscious, give lukewarm water (pint or ½ liter). Do not induce vomiting. Lie down, keep warm and cover eyes to exclude light. <b>Comments:</b> Treat same as methyl alcohol poisoning.			
<b>SECTION 5: FIRE FIGHTING MEASURES</b>			
<b>Flash Point:</b> 46.9° F. / 8.3° C. <b>Fire Hazards:</b> Static electricity may accumulate and ignite vapors. Prevent a possible fire hazard by suitable means, such as bonding or grounding, vapor dilution and the like. Vapors are heavier than air and can travel along the ground to remote ignition sources such as pilot lights. <b>Unusual Fire Hazards:</b> Thermal breakdown of this product during fire or extremely high heat conditions may evolve the following hazardous decomposition products: Silicon Dioxide, Carbon Dioxide, and traces of incompletely burned carbon compounds, trace formaldehyde. <b>Extinguishing Media:</b> Carbon Dioxide (CO <sub>2</sub> ), Water, Dry Chemical. <b>Fire Fighting Procedures:</b> Self contained breathing apparatus and full turn out gear should be worn when fighting fires involving chemicals. Heat exposure pressurizes closed containers. Evacuate area immediately.			

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Containment/Clean-up:** Disposal of collected product, residues and cleanup materials may be governmentally regulated. Observe all applicable local, state and federal waste management regulations. Remove possible ignition sources and if needed, use non-sparking tools and equipment. To prevent spontaneous combustion, store rags, mops, absorbent, etc; used during cleanup only in appropriate containers or covered with water. Mop, wipe or soak up spills with absorbent material and contain for salvage or disposal. For large spills, provide diking or other appropriate containment to keep material from spreading. Clean any remaining slippery surfaces by appropriate techniques, such as washing with mild, caustic detergents or solutions or high pressure steam for larger areas. Observe any safety precautions applicable to the cleaning material used.

## SECTION 7: HANDLING & STORAGE

**Handling:** No special precautions.

**Storage:** Keep container closed and store away from heat, sparks and open flame. Store in a cool, dry area and away from water or moisture.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

**Skin Protection:** Wash at mealtime and end of shift; no special protection is generally needed.

**Eye Protection:** Safety glasses at minimum.

**Respiratory Protection:** Use respiratory protection at all times during handling and application.

**Protective Equipment:** Eyewash station (bottle) should be within direct access of work area.

**Personal Hygiene:** Do not get in eyes or absorbed into clothing. Avoid prolonged contact with skin. Wash thoroughly after handling. Wash contaminated clothing before reuse.

**Engineering Controls:** For in field installations, use local exhaust ventilation when using in enclosed areas. For spray booth installations provide air-sampling data to show exposures are within recommended exposure guidelines. Industrial hygiene personnel can assist in judging the adequacy of engineering controls.

## SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

**pH:** Not Applicable (non-aqueous)

**Solubility in water:** Hydrolyzes

**Appearance:** Clear Liquid

**Odor:** Strong Odor

**Specific Gravity @ 25° C:** 0.95

**Boiling Point:** >35° C., > 95° F.

**Freeze Point:** Not Applicable

**VOC Content:** 613 grams per liter (Components A, B, C mixed) Method 24.

## SECTION 10: STABILITY & REACTIVITY

**Stability:** Stable

**Hazardous Polymerization:** Will not occur.

**Hazardous Decomposition:** None known.

**Conditions to Avoid:** Methyl alcohol forms when exposed to water or humid air.

**Materials to Avoid:** Concentrated mineral acids, strong oxidizers, aldehydes, halogens and halogen compounds.

<b>SECTION 11: TOXICOLOGICAL INFORMATION</b>									
Methyl alcohol forms on contact with water, moisture or humid air. Provide ventilation to control exposure within guidelines of OSHA PEL: TWA 200 ppm and ACGIH TLV – skin: TWA 200 ppm, STEL 250 ppm.									
<b>SECTION 12: ECOLOGICAL INFORMATION</b>									
There is no data available.									
<b>SECTION 13: DISPOSAL CONSIDERATIONS</b>									
Use excess product in an alternate application. Handle disposal of waste material in a manner which complies with local, state, district and federal regulations.									
<b>SECTION 14: TRANSPORT INFORMATION</b>									
<p><b>DOT Information</b> (49 CFR 172.101)</p> <p><b>Proper Shipping Name:</b> COATING SOLUTION</p> <p><b>Hazard Technical Name:</b> ALKOXYSILANES</p> <p><b>Hazard Class:</b> 3</p> <p><b>UN Number:</b> UN1139</p> <p><b>Packing Group:</b> II</p>									
<b>SECTION 15: REGULATORY INFORMATION</b>									
<p><b>TSCA Status:</b> All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of chemical substances.</p> <p><b>EPA SARA Title III Chemical Listings:</b></p> <p><b>Section 302 CERCLA Extremely Hazardous Substances:</b> None</p> <p><b>Section 304 CERCLA Hazardous Substances:</b> None</p> <p><b>Section 312 Hazard Class:</b></p> <p>Acute: Yes Chronic: Yes Fire: Yes Pressure: No Reactive: No</p> <p><b>Section 313 Toxic Chemicals:</b></p> <table border="1"> <thead> <tr> <th><u>C.A.S. Number</u></th> <th><u>Wt%</u></th> <th><u>Ingredient Name</u></th> </tr> </thead> <tbody> <tr> <td>67-56-1</td> <td>&lt;2.0%</td> <td>Methyl Alcohol</td> </tr> </tbody> </table> <p><b>Other U.S. State Regulations:</b></p> <p><b>California Proposition 65:</b> This material does not contain any chemicals known to the State of California to cause cancer or reproductive effects.</p> <p><b>Massachusetts Right-to-Know:</b> This material contains no other listed components; Methyl Alcohol, 67-56-1.</p> <p><b>New Jersey Right-to-Know:</b> This material contains no other listed components; Methyl Alcohol, 67-56-1.</p> <p><b>Pennsylvania Right-to-Know:</b> This material contains no other listed components; Methyl Alcohol, 67-56-1.</p> <p><b>Canadian Regulations:</b></p> <p>This product has been classified by the raw material suppliers in accordance with the Hazard Criteria of the CPR and the MSDS contains all the information required by CPR.</p> <p><b>Canadian WHMIS:</b> None.</p> <p><b>Canadian DSL Status:</b> This material or its components are listed on the Canadian Domestic Substances List.</p> <p><b>Canadian Ingredient Disclosure List:</b> This material contains no other listed components.</p>				<u>C.A.S. Number</u>	<u>Wt%</u>	<u>Ingredient Name</u>	67-56-1	<2.0%	Methyl Alcohol
<u>C.A.S. Number</u>	<u>Wt%</u>	<u>Ingredient Name</u>							
67-56-1	<2.0%	Methyl Alcohol							
<b>Revision Date:</b> February 2012	<b>Prepared by:</b> MSDS Coordinator @ 386-274-1382 Daytona Beach, Florida 32117								

## MATERIAL SAFETY DATA SHEET

<b>SECTION 1: PRODUCT &amp; COMPANY INFORMATION</b>			
<b>Material Identification:</b> MicroGuard AD702 Concrete Clear Waterproofing Sealer (Part B)			
<b>Adsil, Inc.</b> <b>1901 Mason Avenue, Suite #101</b> <b>Daytona Beach, FL 32117</b>	<b>386-274-1382 PHONE</b> <b>386-274-1798 FAX</b> <b>CHEMTREC: 1-800-424-9300</b>		
<b>SECTION 2: OSHA HAZARDOUS INGREDIENTS</b>			
<u>C.A.S. Number</u>	<u>Wt%</u>	<u>Ingredients</u>	<u>Exposure Limits</u>
68412-37-3	78-82%	Polydiethoxysiloxane	TWA 10 ppm
5593-70-4	18-20%	Tetra n-butyl titanate	None Established
<b>SECTION 3: HAZARDS IDENTIFICATION</b>			
<b>NFPA/HMIS Rating:</b> Health 2, Flammability 2, Reactivity 1 <b>Primary Routes of Entry:</b> Skin Contact, Eye Contact, Inhalation, Ingestion <b>Effects of Overexposure:</b> <b>Skin:</b> Causes skin irritation with itching, burning, reddening, swelling or rash. <b>Eyes:</b> May cause severe eye irritation with tearing, pain or blurred vision. <b>Inhalation:</b> May cause irritation of the nose and throat with sneezing, sore throat or runny nose. <b>Ingestion:</b> Get immediate medical attention. Do not induce vomiting.			
<b>SECTION 4: FIRST AID MEASURES</b>			
<b>Skin Contact:</b> Flush skin with water after contact. Wash contaminated clothing before reuse. <b>Eye Contact:</b> Immediately flush with clean water for 15 minutes. Get medical attention. <b>Inhalation:</b> Remove to fresh air. Get medical attention if ill effects persist. <b>Ingestion:</b> If swallowed, do not induce vomiting. Give lukewarm water (pint or ½ liter) if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention. <b>Comments:</b> Treat the same as for methyl alcohol poisoning.			
<b>SECTION 5: FIRE FIGHTING MEASURES</b>			
<b>Flash Point:</b> 145° F. / 63° C. <b>Fire Hazards:</b> If this material is exposed to water or moisture it will react and produce ethyl alcohol. This will cause the flash point to decrease. Such fumes will result from hydrolysis or pyrolysis during use. Use explosion-proof exhaust systems to vent fumes and vapor. <b>Unusual Fire Hazards:</b> Static electricity may accumulate and ignite vapors. Prevent a possible fire hazard by suitable means, such as bonding or grounding equipment, vapor dilution and the like. Vapors are heavier than air and can travel along the ground to remote ignition sources. Extinguish all pilot lights in the immediate area. <b>Extinguishing Media:</b> Foam, Dry Chemical or CO <sub>2</sub> . <b>Fire Fighting Procedures:</b> Self-contained breathing apparatus and full turn out gear should be worn when fighting fires involving chemicals.			
<b>SECTION 6: ACCIDENTAL RELEASE MEASURES</b>			
<b>Containment/Clean-up:</b> Disposal of collected product, residues and cleanup material may be governmentally regulated. Observe all applicable local, state, district and federal waste management regulations. Remove any possible ignition sources. Mop, wipe or soak up spills with absorbent material and contain for salvage or disposal. For large spills, provide diking or other appropriate containment to keep material from spreading. Clean any remaining slippery surfaces by appropriate techniques, such as washing with mild, caustic detergents or solutions or high pressure steam and extraction for larger areas. Observe any safety precautions applicable to the cleaning material used.			

<b>SECTION 7: HANDLING &amp; STORAGE</b>
<p><b>Handling:</b> No special precautions.</p> <p><b>Storage:</b> Keep container closed and away from heat, sparks and open flame. Store away from water or moisture. Store in a cool, dry area.</p>
<b>SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION</b>
<p><b>Skin Protection:</b> Wear Nitrile gloves during handling. Wash at mealtime and end of shift.</p> <p><b>Eye Protection:</b> Safety glasses at minimum.</p> <p><b>Respiratory Protection:</b> Use respiratory protection at all times during handling and application.</p> <p><b>Protective Equipment:</b> Eyewash station (bottle) should be within direct access of work area.</p> <p><b>Personal Hygiene:</b> Do not get in eyes or absorbed into clothing. Avoid prolonged contact with skin. Wash thoroughly after handling. Wash contaminated clothing before reuse.</p> <p><b>Engineering Controls:</b> For in field installation, use local exhaust ventilation when using in enclosed areas. For spray booth installations provide air-sampling data to show exposures are within recommended exposure guidelines. Industrial hygiene personnel can assist in judging the adequacy of engineering controls.</p>
<b>SECTION 9: PHYSICAL &amp; CHEMICAL PROPERTIES</b>
<p><b>pH:</b> Not Applicable (non-aqueous)</p> <p><b>Solubility in water:</b> Hydrolyzes</p> <p><b>Appearance:</b> Clear Liquid to Pale Yellow.</p> <p><b>Odor:</b> Moderate Odor.</p> <p><b>Specific Gravity @ 25° C.:</b> 1.05</p> <p><b>Boiling Point:</b> 169° C., 340° F.</p> <p><b>Freeze Point:</b> Not Applicable</p> <p><b>VOC Content:</b> 613 grams per liter (Components A, B, C mixed); Method 24.</p>
<b>SECTION 10: STABILITY &amp; REACTIVITY</b>
<p><b>Stability:</b> Stable.</p> <p><b>Hazardous Polymerization:</b> Condition leading to polymerization is hydrolysis. Not a hazard.</p> <p><b>Hazardous Decomposition:</b> None known.</p> <p><b>Conditions to Avoid:</b> Heating can generate olefins and other flammable organic compounds.</p> <p><b>Materials to Avoid:</b> Incompatible with water. Hydrolyzes very rapidly forming butanol.</p>
<b>SECTION 11: TOXICOLOGICAL INFORMATION</b>
There is no data available.
<b>SECTION 12: ECOLOGICAL INFORMATION</b>
There is no data available.
<b>SECTION 13: DISPOSAL CONSIDERATIONS</b>
Use excess product in an alternate application. Handle disposal of waste material in a manner which complies with local, state, district and federal regulations.
<b>SECTION 14: TRANSPORT INFORMATION</b>
<p><b>DOT Information (49 CFR 172.101):</b></p> <p><b>Proper Shipping Name:</b> COATING SOLUTION</p> <p><b>Hazard Technical Name:</b> ALKOXYSILANE</p> <p><b>Hazard Class:</b> 3</p> <p><b>UN Number:</b> UN1139</p> <p><b>Packing Group:</b> II</p>

**SECTION 15: REGULATORY INFORMATION**

**TSCA Status:** All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**EPA SARA Title III Chemical Listings:**

**Section 302 CERCLA Extremely Hazardous Substances:** None.

**Section 304 CERCLA Hazardous Substances:** None.

**Section 312 Hazard Class:**

Acute: Yes

Chronic: Yes

Fire: Yes

Pressure: No

Reactive: No

**Section 313 Toxic Chemicals:** None.

**Other U.S. State Regulations:**

**California Proposition 65:** This material does not contain any chemicals known to the State of California to cause cancer or reproductive effects.

**Massachusetts Right-to-Know:** This material contains no listed components.

**New Jersey Right-to-Know:** This material contains no listed components.

**Pennsylvania Right-to-Know:** This material contains no listed components.

**Canadian Regulations:**

This product has been classified by the raw material suppliers in accordance with the Hazard Criteria of the CPR and the MSDS contains all the information required by CPR.

**Canadian WHMIS:** None.

**Canadian DSL Status:** This material or its components are listed on the Canadian Domestic Substances List.

**Canadian Ingredient Disclosure List:** This material contains no listed components.

**Revision Date:** February 2012

**Prepared by:** MSDS Coordinator @ 386-274-1382  
Daytona Beach, Florida 32117

## MATERIAL SAFETY DATA SHEET

<b>SECTION 1: PRODUCT &amp; COMPANY INFORMATION</b>			
<b>Material Identification:</b> MicroGuard AD702 Concrete Clear Waterproofing Sealer (Part C)			
<b>Adsil, Inc.</b> 1901 Mason Avenue, Suite #101 Daytona Beach, FL 32117	<b>386-274-1382 PHONE</b> <b>386-274-1798 FAX</b> <b>CHEMTREC: 1-800-424-9300</b>		
<b>SECTION 2: OSHA HAZARDOUS INGREDIENTS</b>			
<u>C.A.S. Number</u>	<u>Wt%</u>	<u>Ingredients</u>	<u>Exposure Limits</u>
67-63-0	20-22%	Isopropyl Alcohol	TWA 400 ppm, STEL 500 ppm
52125-53-8	18-20%	Glycol Ether PE	Not Established
1569-01-3	16-18%	Glycol Ether PNP	Not Established
7732-18-5	42-44%	DI Water	None
<b>SECTION 3: HAZARDS IDENTIFICATION</b>			
<b>NFPA/HMIS Rating:</b> Health 1, Flammability 2, Reactivity 0 <b>Primary Routes of Entry:</b> Skin Contact, Eye Contact, Inhalation, Ingestion <b>Effects of Overexposure:</b> <b>Skin:</b> May cause skin irritation. <b>Eyes:</b> Causes eye irritation. <b>Inhalation:</b> Prolonged inhalation of spray mist can cause damage to respiratory tract. <b>Ingestion:</b> May cause irritation to gastrointestinal tract causing abdominal pain and vomiting. <b>Signs &amp; Symptoms of Exposure:</b> Burning pain in the nose and throat (inhalation), pain, redness and tearing (eye exposure), itching or burning (skin exposure).			
<b>SECTION 4: FIRST AID MEASURES</b>			
<b>Skin Contact:</b> No first aid should be needed. If itching or burning occurs, wash area with soap and water. <b>Eye Contact:</b> Immediately flush with clean water for 15 minutes. Get medical attention. <b>Inhalation:</b> Remove to fresh air. Get medical attention if ill effects persist. <b>Ingestion:</b> Get medical attention immediately. Do not induce vomiting. Risk of damage to lungs exceeds poisoning risk. If large quantity is swallowed, give pint or ½ liter of lukewarm water if victim is conscious. Lie down, keep warm and cover eyes to exclude light. <b>Comments:</b> Treat the same as methyl alcohol poisoning.			
<b>SECTION 5: FIRE FIGHTING MEASURES</b>			
<b>Flash Point:</b> 62.0° F. / 13.7° C. <b>Fire Hazards:</b> Static electricity may accumulate and ignite vapors. Prevent a possible fire hazard by suitable means, such as bonding and grounding, inert gas purge, vapor dilution and the like. Vapors are heavier than air and can travel along the ground to remote ignition sources. Extinguish all pilot lights in vicinity. <b>Unusual Fire Hazards:</b> Thermal breakdown of this product during fire or extremely high heat conditions may evolve the following hazardous decomposition products: Silicon Dioxide, Carbon Dioxide and traces of incompletely burned carbon products, Nitrogen Oxides, Formaldehyde. <b>Extinguishing Media:</b> Carbon Dioxide (CO <sub>2</sub> ), Water Fog, Dry Chemical. <b>Fire Fighting Procedures:</b> Self contained breathing apparatus and full turn out gear should be worn when fighting fires involving chemicals. Heat exposure pressurizes closed containers. Evacuate area immediately.			

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Containment/Clean-up:** Disposal of collected product, residues and cleanup materials may be governmentally regulated. Observe all applicable local, state, district and federal waste management regulations. Remove possible ignition sources and if needed, use non-sparking equipment. Mop, wipe or soak up with absorbent material and contain for salvage or disposal. For large spills, provide diking or other means of containment to keep material from spreading. Clean any remaining slippery surfaces by appropriate techniques, such as washing with mild, caustic detergents or solutions, or high-pressure steam for larger areas. Observe any safety precautions applicable to the cleaning material used. Use full-face respirator and suitable protective wear.

## SECTION 7: HANDLING & STORAGE

**Handling:** No special precautions.

**Storage:** Keep the container closed and away from heat, sparks and open flame. Store away from water or moisture. Store in cool, dry area.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

**Skin Protection:** Wash at mealtime and end of shift; no special protection is generally needed.

**Eye Protection:** Safety glasses at minimum.

**Respiratory Protection:** Use respiratory protection at all times during handling and application.

**Protective Equipment:** Eyewash station (bottle) should be within direct access of work area.

**Personal Hygiene:** Do not get in eyes or absorbed into clothing. Avoid prolonged exposure with skin. Wash thoroughly after handling. Wash contaminated clothing before reuse.

**Engineering Controls:** For in field installations, use local exhaust ventilation when using in enclosed areas. For spray booth installations provide air-sampling data to show exposures are within recommended exposure guidelines. Industrial hygiene personnel can assist in judging the adequacy of engineering controls.

## SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

**pH:** Not Applicable.

**Solubility in water:** Complete.

**Appearance:** Colorless to Very Pale Yellow.

**Odor:** Moderate Odor (alcohol).

**Specific Gravity @ 25° C:** 0.89

**Boiling Point:** 90° C., 194° F.

**Freeze Point:** Not Applicable.

**VOC Content:** 613 grams per liter (Components A, B, C mixed) Method 24.

## SECTION 10: STABILITY & REACTIVITY

**Stability:** Stable.

**Hazardous Polymerization:** Will not occur.

**Hazardous Decomposition:** None known.

**Conditions to Avoid:** None known.

**Materials to Avoid:** None known.



<b>SECTION 11: TOXICOLOGICAL INFORMATION</b>	
There is no data available.	
<b>SECTION 12: ECOLOGICAL INFORMATION</b>	
There is no data available.	
<b>SECTION 13: DISPOSAL CONSIDERATIONS</b>	
Use excess product in an alternate application. Handle disposal of waste material in a manner which complies with local, state, district and federal regulations.	
<b>SECTION 14: TRANSPORT INFORMATION</b>	
<p><b>DOT Information</b> (49 CFR 172.101)</p> <p><b>Proper Shipping Name:</b> COATING SOLUTION</p> <p><b>Hazard Technical Name:</b> SOLVENT MIXTURE</p> <p><b>Hazard Class:</b> 3</p> <p><b>UN Number:</b> UN 1139</p> <p><b>Packing Group:</b> II</p>	
<b>SECTION 15: REGULATORY INFORMATION</b>	
<p><b>TSCA Status:</b> All chemical substances in this material are included on or exempt from listing on the TSCA Inventory of Chemical Substances.</p> <p><b>EPA SARA Title III Chemical Listings:</b></p> <p><b>Section 302 CERCLA Extremely Hazardous Substances:</b> None.</p> <p><b>Section 304 CERCLA Hazardous Substances:</b> None.</p> <p><b>Section 312 Hazard Class:</b></p> <p>Acute: Yes</p> <p>Chronic: Yes</p> <p>Fire: Yes</p> <p>Pressure: No</p> <p>Reactive: No</p> <p><b>Section 313 Toxic Chemicals:</b> None.</p> <p><b>Other U.S. State Regulations:</b></p> <p><b>California Proposition 65:</b> This material does not contain any chemicals known to the State of California to cause cancer or reproductive effects.</p> <p><b>Massachusetts Right-to-Know:</b> This material contains no other listed components.</p> <p><b>New Jersey Right-to-Know:</b> This material contains no other listed components.</p> <p><b>Pennsylvania Right-to-Know:</b> This material contains no other listed components.</p> <p><b>Canadian Regulations:</b></p> <p>This product has been classified by the raw material suppliers in accordance with the Hazard Criteria of the CPR and the MSDS contains all the information required by CPR.</p> <p><b>Canadian WHMIS:</b> None.</p> <p><b>Canadian DSL Status:</b> This material or its components are listed on the Canadian Domestic Substances List.</p> <p><b>Canadian Ingredient Disclosure List:</b> This material contains no other listed components.</p>	
<b>Revision Date:</b> February 2012	<b>Prepared by:</b> MSDS Coordinator @ 386-274-1382 Daytona Beach, Florida 32117